



Product Highlights

- Capacity up to 6TB
- Support for up to 64 cameras per drive
- AllFrame™ technology
- MTBF of up to 1.5 million hours
- 3-year limited warranty

INTERFACE
SATA 6 Gb/s

PERFORMANCE CLASS
5400 / 7200 RPM Class

FORM FACTOR
3.5-inch

CAPACITIES
2TB to 6TB

MODEL NUMBERS

SUB-CR2000W SUB-CR4000S
SUB-CR3000W SUB0CR6000S

THE WESTERN DIGITAL ADVANTAGE

Western Digital puts our products through extensive Functional Integrity Testing (F.I.T.) prior to any product launch. This testing ensures our products consistently meet the highest quality and reliability standards of the Western Digital brand.

Western Digital also has a detailed Knowledge Base with more than 1,000 helpful articles as well as software and utilities. Our customer support lines have long operational hours to ensure you get the help you need when you need it. Our toll-free customer support lines are here to help, or you can access our Western Digital Support site for additional details.

WD Purple™ drives are built for 24/7, always-on, high-definition security systems. WD Purple™ surveillance storage feature Western Digital's exclusive AllFrame™ technology, so you can confidently create a security system tailored to the needs of your business. Using AllFrame™ technology, WD Purple™ drives improve video capturing and help to reduce errors, pixelation, and video interruptions that could happen in a video recorder system. WD Purple drives have an enhanced workload rating that supports systems designed for 24x7 video recording with up to 64 cameras.

Industry-leading storage. Surveillance you can trust.

Western Digital is a worldwide leader in the hard drive industry. With WD Purple surveillance storage, you have a drive engineered for high temperature, always-on surveillance systems so you can rely on quality video playback when you need it most. Whether you're protecting loved ones or monitoring your business, WD Purple offers performance you can trust.

Western Digital's Exclusive AllFrame Technology

All WD Purple drives are equipped with AllFrame technology, which improves ATA streaming to help reduce frame loss, improve overall video playback, and increase the number of hard drive bays supported within a NVR. Make your surveillance solution future-ready knowing that WD Purple drives are ready for ultra high definition cameras. WD Purple capacities up to 6TB feature AllFrame 4K technology enabling high quality recording for up to 64 cameras.

Enhanced Workload Ratings

WD Purple drives with AllFrame 4K technology feature a workload rating of up to 180TB/year - up to three times that of desktop drives - to handle the unique demands of modern video surveillance DVR and NVR systems. WD Purple with AllFrame AI feature a workload rating up to 360TB/year to support the Deep Learning analytics that is featured in AI capable NVRs.

Expand your view to 64

Each WD Purple drive is optimized to support up to 64 cameras. With so many options, you have the flexibility to upgrade or expand your security system in the future.

Designed for Today's and Tomorrow's Surveillance Solutions

With an MTBF of up to 1.5 million hours¹, WD Purple drives are engineered for mainstream surveillance DVRs and NVRs that operate 24/7. With support for more than eight bays² and tarnish resistant components², WD Purple drives deliver reliable operation in large scale surveillance systems in harsh environments.

Wide Compatibility. Seamless Integration.

WD Purple hard drives are built with compatibility in mind, so you can quickly and seamlessly add capacity to your surveillance system. With a wide range of industry-leading enclosures and chipsets supported, you're sure to find the DVR or NVR configuration that's right for you.

Three Year Limited Warranty

As an industry-leading hard drive manufacturer, WD stands behind their surveillance storage solutions with a 3-year limited warranty included with every WD Purple drive.

Specifications⁵

	4TB	3TB	2TB
Model Number⁴	SUB-CR4000S	SUB-CR3000W	SUB-CR2000W
Formatted capacity ⁵	4TB	3TB	2TB
Form factor	3.5-inch	3.5-inch	3.5-inch
Advanced Format (AF)	Yes	Yes	Yes
RoHS compliant ⁶	Yes	Yes	Yes
Product Features			
Cameras supported	Up to 64	Up to 64	Up to 64
Drive Bays Supported	8+	8	8
AI Streams	--	--	--
Firmware Feature Name	AllFrame 4K	AllFrame 4K	AllFrame 4K
Tarnish resistant components	Yes	No	No
Performance			
Interface transfer rate (max) ⁵			
Buffer to host	6 Gb/s	6 Gb/s	6 Gb/s
Host to/from drive (sustained)	150 MB/s	145 MB/s	145 MB/s
Cache (MB) ⁵	64	64	64
Performance Class	5400 RPM	5400 RPM	5400 RPM
Reliability/Data Integrity			
Load/unload cycles ⁷	300,000	300,000	300,000
Annualized workload rating ⁸	180TB/yr	180TB/yr	180TB/yr
Non-recoverable read errors per bits read	<1 in 10 ¹⁴	<1 in 10 ¹⁴	<1 in 10 ¹⁴
MTBF	1,000,000	1,000,000	1,000,000
Limited warranty (years) ⁹	3	3	3
Power Management¹⁰			
Average power requirements (W)			
Read/Write	5.1	4.4	4.4
Idle	4.5	4.1	4.1
Standby and Sleep	0.4	0.4	0.4
Environmental Specifications¹¹			
Temperature (°C, on the base casting)			
Operating ¹²	0 to 65	0 to 65	0 to 65
Non-operating	-40 to 70	-40 to 70	-40 to 70
Shock (Gs)			
Operating (2 ms, read/write)	30	30	30
Operating (2 ms, read)	65	65	65
Non-operating (2 ms)	250	250	250
Acoustics (dBA) ¹³			
Idle	25	23	23
Seek (average)	28	24	24
Physical Dimensions			
Height (in./mm, max)	1.028/26.1	1.028/26.1	1.028/26.1
Length (in./mm, max)	5.787/147	5.787/147	5.787/147
Width (in./mm, ± .01 in.)	4/101.6	4/101.6	4/101.6
Weight (lb/kg, ± 10%)	1.50/0.68	1.40/0.64	1.32/0.60

¹ Up to 1.5M MTBF for 8TB, 10TB, 12TB and 14TB capacities (up to 1.0M MTBF for lower capacities). MTBF specifications are based upon internal testing using a 40°C base casting temperature. MTBF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTBF does not predict an individual drive's reliability and does not constitute a warranty.

² For capacities 4TB and higher.

³ As of April 2018

⁴ Not all products may be available in all regions of the world.

⁵ As used for storage capacity, one gigabyte (GB) = one billion bytes and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 6 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

⁶ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁷ Controlled unload at ambient condition.

⁸ Workload Rate is defined as the amount of user data transferred to or from the hard drive. Workload Rate is annualized (TB transferred x (8760 / recorded power-on hours)). Workload Rate will vary depending on your hardware and software components and configurations.

⁹ See support.wdc.com/warranty for regional specific warranty details.

¹⁰ Power measurements at room-ambient temperature.

¹¹ No non-recoverable errors during operating tests or after non-operating tests.

¹² On the base casting.

¹³ Sound power level.

Western Digital.

5601 Great Oaks Parkway
San Jose, CA 95119, USA

www.westerndigital.com

© 2020 Western Digital Corporation or its affiliates. All rights reserved. Western Digital, the Western Digital logo, AllFrame 4K, IntelliSeek, F.I.T. Lab, HelioSeal and WD Purple are registered trademarks or trademarks of Western Digital Corporation or its affiliates in the US and/or other countries. All other marks are the property of their respective owners. Product specifications subject to change without notice. Picture shown may vary from actual product. Not all products are available in all regions of the world.

Specifications⁵

	6TB
Model Number ⁴	SUB0CR6000S
Formatted capacity ⁵	6TB
Form factor	3.5-inch
Advanced Format (AF)	Yes
RoHS compliant ⁶	Yes
Product Features	
Cameras supported	Up to 64
Drive Bays Supported	8+
AI Streams	--
Firmware Feature Name	AllFrame 4K
Tarnish resistant components	Yes
Performance	
Interface transfer rate (max) ⁵	
Buffer to host	6 Gb/s
Host to/from drive (sustained)	175 MB/s
Cache (MB) ⁵	64
Performance Class	5400 RPM
Reliability/Data Integrity	
Load/unload cycles ⁷	300,000
Annualized workload rating ⁸	180TB/yr
Non-recoverable read errors per bits read	<1 in 10 ¹⁴
MTBF	1,000,000
Limited warranty (years) ⁹	3
Power Management ¹⁰	
Average power requirements (W)	
Read/Write	5.3
Idle	4.9
Standby and Sleep	0.4
Environmental Specifications ¹¹	
Temperature (°C, on the base casting)	
Operating ¹²	0 to 65
Non-operating	-40 to 70
Shock (Gs)	
Operating (2 ms, read/write)	30
Operating (2 ms, read)	65
Non-operating (2 ms)	250
Acoustics (dBA) ¹³	
Idle	25
Seek (average)	28
Physical Dimensions	
Height (in./mm, max)	1.028/26.1
Length (in./mm, max)	5.787/147
Width (in./mm, ± .01 in.)	4/101.6
Weight (lb/kg, ± 10%)	1.65/0.75

¹ Up to 1.5M MTBF for 8TB, 10TB, 12TB, and 14TB capacities (up to 1.0M MTBF for lower capacities). MTBF specifications are based upon internal testing using a 40°C base casting temperature. MTBF is based on a sample population and is estimated by statistical measurements and acceleration algorithms. MTBF does not predict an individual drive's reliability and does not constitute a warranty.

² For capacities 4TB and higher.

³ As of April 2018

⁴ Not all products may be available in all regions of the world.

⁵ As used for storage capacity, one gigabyte (GB) = one billion bytes and one terabyte (TB) = one trillion bytes. Total accessible capacity varies depending on operating environment. As used for buffer or cache, one megabyte (MB) = 1,048,576 bytes. As used for transfer rate or interface, megabyte per second (MB/s) = one million bytes per second, and gigabit per second (Gb/s) = one billion bits per second. Effective maximum SATA 6 Gb/s transfer rate calculated according to the Serial ATA specification published by the SATA-IO organization as of the date of this specification sheet. Visit www.sata-io.org for details.

⁶ WD hard drive products manufactured and sold worldwide after June 8, 2011, meet or exceed Restriction of Hazardous Substances (RoHS) compliance requirements as mandated by the RoHS Directive 2011/65/EU.

⁷ Controlled unload at ambient condition.

⁸ Workload Rate is defined as the amount of user data transferred to or from the hard drive. Workload Rate is annualized (TB transferred x (8760 / recorded power-on hours)). Workload Rate will vary depending on your hardware and software components and configurations.

⁹ See support.wdc.com/warranty for regional specific warranty details.

¹⁰ Power measurements at room-ambient temperature.

¹¹ No non-recoverable errors during operating tests or after non-operating tests.

¹² On the base casting.

¹³ Sound power level.