

## **DirectNet™ Switch** 28 Ports



## Features: Description: The CRIS28V2 PoE switche is designed to seamlessly connect to the Costar XDi Series Network • Supports 4 SFP Slots • Maximum per 370W Avaiable Video Recorders. The simple plug and play function-• IEEE 802.3af, IEEE 802.3at ality makes connection to the XDi recorder fast and easy, eliminating the need for a computer to program or trouble shoot the switch. The application layer is designed to work with the XDi Series and is preconfigured for the DirectNET interface. The switches monitor and report the power consumption and location of each DirectNET camera. The switches are designed for the constant bandwidth required for video steaming.

- Supports 24 RJ45 Connectors



## **CRIS28V2 Specifications**

Model	Total Ports	PoE Ports
CRIS28V2	28 Port PoE Switch	24 RJ45

Power		
Source	AC 100 ~ 240 VAC	
Consumption	460W	
Rated Input	AC 100 ~ 240V, 50/60 Hz 5.5A ~ 2.5A	
System Information		
CPU	1Ghz single Core	
System Memory	512MB SDRAM, 256 Flash	
Switching Capacity	56Gbps	
Copper Service Port	24 RJ45 Connectors 10/100/1000BASE-T	
Optical Uplink Port	4 SFP Slots 1000BASE-X	
PoE Power		
Supported Standards	IEEE 802.3af-2003 IEEE 802.3at-2009	
Poe Device Connections	up to 24 IEEE 802.3af or up to 12 IEEE 802.3at	

General Information				
Approvals	FCC, CE, KC			
Humidity	10% ~ 90%			
Temperature	-32°F ~ 131°F			
Dimensions W x H x D	17.3" x 1.7" x 10.2"			
Weight	9.42lbs			
Dimensions				
17.3″				

