

26" LED Public View Monitor 4 Megapixel Resolution



Description:

The CMC26LEDPVIP public view monitor provides high quality 4 megapixel resolution. The monitor weighs 17 lbs. and has a standard VESA mounting pattern which will accommodate a wide variety of wall or ceiling mounts. This public view monitor is an ideal choice for retail, banking, convenience stores, fast food and many other commercial applications.

Costar's IP cameras are compatible with the StarNET Video Management Software (VMS). The StarNET user interface incorporates features such as simplified user management, advanced camera mapping and logical camera grouping making it easier to monitor and access each of your cameras. The StarNET user interface also has the ability to integrate both analog and IP camera technology on the same platform allowing you to have a diverse surveillance system. Costar's IP cameras are ONVIF supported. The industry standard ONVIF protocol makes it easy to integrate Costar branded IP cameras with ONVIF compatible recorders.


Features:

- 26" LED backlit monitor
- 4 megapixel resolution (1080p Full-HD)
- 2.8-12 mm DC auto-iris lens
- 1/2.8" CMOS Progressive Scan image sensor
- ONVIF supported; StarNET compatible
- Metal housing with anti-glare protection glass
- IR motion detection sensor
- 3D Digital Noise Reduction (3DNR)
- 3D comb filter
- 17 lbs.
- AC110V

CMC26LEDPVIP Specifications

Model	Lens (mm)	Resolution
CMC26LEDPVIP	2.8-12 mm	4 megapixel

Power	
Power Source	AC110V
Power Consumption	60 Watt max
Camera Features	
Image Sensor	1/2.8" CMOS Progressive Scan
Lens	2.8-12 mm fixed mega pixel
Minimum Illumination	Color: 1.0 Lux (F1.2)
Resolution	4 MP (2560 x 1440) 2 MP (1920x1080) HD (1280x720) VGA (640x352) CIF (320x176) QCIF (160x96)
Frame Rate	Up to 30 fps
Camera Features	
Resolution	2560 x 1440
LCD Panel	26" diagonal
Viewing Angle	170° H x 170° V
Display Colors	16.7 million
Contrast Ratio	3000:1
Brightness	500cd/m ²
Response Time	5 ms
Video Input / Output	
Video Compression	H.264, MJPEG
Video Streaming	Dual Stream
Video Standards	OnVIF, PSIA
Composite Inputs	2 BNC, VGA, HDMI
Composite Outputs	2 BNC
Audio	2 Input
Speaker	2 2.5 Watt
3D Comb Filter	Yes
3DNR	Yes
PIP/POP	Yes

General Information	
Operating Temperature	32°F to 122°F (0°C to 50°C)
Operating Humidity	80% RH Max
Accessories	Power cord, adapter
Auto adjustment	Yes
OSD Control	Yes
OSD Language	Multiple
Remote Control	Yes
Weight	17 lbs.
Dimensions (w x h x d)	24.5" x 17.31" x 3.75"
Applications	
	iNEX Connect and manage IP and Analog cameras on a single user interface.

COSTAR
VIDEO SYSTEMS

101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com

Specifications and design are subject to change without notice. Conversions: 1" = 25.4mm Measurement conversions are approximate.