

32" LED TVI Public View Monitor 2 Megapixel



Description:

The CMT32PVM is a 32" public view monitor that provides high quality 2 megapixel resolution with a built-in TVI camera. The monitor weighs 17 lbs. and has a standard pattern VESA mounting which accommodate a wide variety of wall or ceiling mounts. This public view monitor is an ideal choice for retail, banking, convenience stores, fast food and many other commercial applications. ΑII Costar cameras compatible with the StarNET Video Management Software platform. StarNET incorporates features such as simplified user management, advanced camera mapping and logical camera grouping making it easier to monitor and access each of your cameras. The StarNET user interface can integrate both CVBS and HD over coax camera technology on the same platform allowing you to have a diverse surveillance system.

Features:

- 32" LED backlit monitor
- 2 megapixel resolution (1080p Full-HD)
- 3.6mm fixed lens
- 1/3" CMOS Progressive Scan image sensor
- Metal housing with anti-glare protection glass
- IR motion detection sensor
- 3D Digital Noise Reduction (3DNR)
- 3D comb filter
- Weight: 17 lbs.
- Power requirement: AC110V



CMT32PVM Specifications

Model	Lens (mm)	Resolution
CMT32PVM	3.6mm	2 megapixel

Power		
Power Source	AC110V	
Power Consumption	60 Watt max	
·	oo wati max	
Camera Features		
Image Sensor	1/3" CMOS Progressive Scan	
Lens	3.6mm fixed megapixel	
Minimum Illumination	Color: 1.0 Lux (F1.2)	
Resolution	2 MP (1920x1080)	
Frame Rate	Up to 30 fps (NTSC) Up to 25 fps (PAL)	
WDR	120dB	
Monitor Features		
Resolution	1920 x 1080	
LCD Panel	26" diagonal	
Viewing Angle	170° H x 170° V	
Display Colors	16.7 million	
Contrast Ratio	3000:1	
Brightness	500cd/m ²	
Response Time	5 ms	
Video Input / Output		
Composite Inputs	2 BNC (Analog), 1 BNC (TVI), VGA, HDMI	
Composite Outputs	2 BNC	
Audio	2 Input	
Speaker	2 2.5 Watt	
3D Comb Filter	Yes	
3DNR	Yes	
PIP/POP	Yes	
Mounting Hardware (optional)		
CMC2600WM Flat Wall Mount	VESA Standard 100 x 100mm	
rial Wall Moutil	200 x 200mm	

General Information		
Operating Temperature	32°F to 122°F (0°C to 50°C)	
Operating Humidity	80% RH Max	
Accessories	Power cord, adapter	
Auto adjustment	Yes	
OSD Control	Yes	
OSD Language	Multiple	
Remote Control	Yes	
Weight	17 lbs.	
Dimensions (w x h x d)	24.5" x 17.31" x 3.75"	

