CBT2312IRFW



2 Megapixel Outdoor IR Bullet Camera Remote Focus HD Over Coax / HD-TVI



		D	
COAX			

Description:	Features:
The CBT2312IRFW outdoor bullet camera provides high quality video at 2 megapixel resolution over existing coaxial cable. The infrared LEDs provide illumination for clear image quality at night. The IP66 weatherproof rating makes this bullet camera suitable for outdoor applications. Costar's new line of HD- TVI cameras are compatible with the ET Series DVRs and iRAS Video Management Software. iRAS is the remote access software that allows users to remotely view live and recorded video. iRAS incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.	 2 megapixel resolution (1080p) 1/2.8" Sony Exmor CMOS image sensor 2.8 - 12 mm remote focus and zoom lens 36 IR LEDs with an 80 foot (25 m) range True day/night with IR cut filter Back Light Compensation (BLC) Digital Noise Reduction (DNR) Wide Dynamic Range (WDR) Up-the-coax control (UTC) Weatherproof IP66 rated Vandal resistant housing IK10 rated DC12V or AC24V



101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

CBT2312IRFW Specifications


Model	Lens (mm)	Resolution
CBT2312IRFW	2.8 - 12 mm	2 Megapixel

Power			
Source	DC12V or AC24V		
Consumption	600mA @ DC12V 200mA @ AC24V IRs On		
Sensor and General Information			
Image Sensor	1/2.8" Sony Exmor CMOS		
Scanning Mode	Progressive Scan		
Resolution (H x V)	1920 x 1080		
Len Type	Remote Focus		
Lens Focal Length	2.8 - 12 mm		
Iris Control	DC Auto Iris		
Frame Rate	Up to 30 fps		
IR LEDs	36 LEDs		
IR Range	80 feet (25 m) range		
IR Spectrum	850nm/45° x &5 x 36 IRs		
Minimum Illumination	0 Lux with IRs On		
Shutter Speed	Auto / Manual / Flicker 1/30 ~ 1/30,000		
S/N Ratio	>50 dB		
Video Features			
Video Output	1.0Vp-p, 75Ω Composite 1.0Vp-p, 75Ω TVI		
Camera Functions			
Auto Gain Control	Yes		
Auto White Balance	Yes		
Back Light Compensation	Yes		
Day / Night	Yes; IR cut filter		
Digital Noise Reduction	Yes		
Wide Dynamic Range	Yes		

General Information

IP Rating	IP66	
IK Rating	IK10	
Humidity	0% ~ 80%	
Temperature	14°F to 122°F	
Temperature	(-10°C to 50°C)	
Dimensions (© x H)	3.9" x 4.9" x 9.4"	
	(99 x 124 x 238 mm)	
Weight	3.0 lbs.	
Weight	(1400 g)	

Line Drawing





101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com