

FlexDome™ Series Indoor Cameras



Description:

The Costar FlexDome Series has long established itself as an outstanding general purpose high resolution camera line. With superior image quality, 700 lines of resolution, and digital wide dynamic range, this line has many years of proven success. The CDC3128IC general purpose 2.8-12mm lens offers the perfect option for wide angle and mid-range viewing solutions. When security performance is critical, depend on the proven quality of the Costar FlexDome.

The FlexDome product line was developed to offer flexible analog solutions. This product line consists of cameras with indoor or outdoor /vandal housings with customizable options such as chassis color and add-on accessories like IR, UTP modules, and heaters.

The FlexDome product line is compatible with our Digital Video Recorders (DVRs) that run our free iRAS Video Management Software (VMS). iRAS is the remote access software that allows users to remotely view live and recorded video. iRAS incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

Features:

- 700 TV Lines of resolution
- Indoor Housing (Cool Grey)
- 2.8 - 12 mm Lens
- DC Auto Iris Lens
- Day/Night (D/N)
- Wide Dynamic Range (D-WDR)
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- Unshielded Twisted Pair UTP (optional)
- 12VDC / 24VAC

CDC3128IC Specifications

Model	Lens	Resolution
CDC3128IC	2.8 - 12 mm	700TVL

CDC3128IB = Black Housing
 CDC3128IW = White Housing

Power	
Power Source	12VDC / 24VAC
Power Consumption	1.5 Watts
Sensor	
Image Sensor	1/3" Panasonic 960H CCD Sensor
Active Pixels Number	518k pixels
Scanning Mode	Progressive Scan
Resolution	700TVL
Video Output	1.0 Vp-p (75Ω Load)
Minimum Illumination	Color: 0.1 Lux B&W: 0.01 Lux
Shutter Speed	1/60 ~ 1/120,000 sec
Scanning Frequency	59.94Hz
S/N Ratio	≥ 50dB
Camera Functions	
Auto Gain Control	Yes
Auto White Balance	Yes
Back Light Compensation	Yes
Day / Night	Yes
Digital Noise Reduction	Yes; 2DNR
Maximizer	No
Motion Detection	Yes; 4 zones
Privacy Masking	Yes; 8 zones
Wide Dynamic Range	Yes; Digital-WDR

General Information	
Temperature	-14°F to +140°F (-10°C to +60°C)
Humidity	85% RH Max
Weight	1.03 lbs. (450g)
Dimensions	Ø5.27" (134mm)
Weight	2.09 lbs. (0.95kg)
Power Input	2-Point Screw
Video Output	BNC Connector
Lens Mount	Fixed Mount
Certifications	FCC, CE
Video test port with test cable and BNC connector	
Mounting pattern matches 40 conduit box	
3-axis gimbal mounting bracket	
Optional trim ring covers a 6 ½" hole	

Dimensions	

Accessory	
CD3000CM	Drop ceiling support plate for use with pendant mounts
CD3000WPM	Wall mount
CDCFLEXIT	Trim ring (white)
CDCFLEXITB	Trim ring (black)
CDMCP	Pendant mount (white)
CDMCPB	Pendant mount (black)

COSTAR
 VIDEO SYSTEMS

101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com

Specifications and design are subject to change without notice. Conversions: 1" = 25.4mm. Measurement conversions are approximate.

Rev. 12/04/16