

2 Megapixel
Outdoor IR Dome Camera
Remote Focus
HD Over Coax / HD-TVI





Description:

The CDT2312VIRFW outdoor dome camera provides high quality video at 2 megapixel resolution over existing coaxial cable. The infrared LEDs provide illumination for clear image quality at night. The IP67 weatherproof rating makes this dome camera suitable for outdoor applications. Costar's new line of HDTVI cameras are compatible with the ET Series DVRs and iRAS Video Management Software. iRAS is the remote access software that allows users to remotely view live and recorded video. iRAS incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

Features:

- 2 megapixel resolution (1080p)
- 1/2.8" Sony Exmor CMOS image sensor
- 2.8 12 mm remote focus and zoom lens
- 42 IR LEDs with a 65 foot (20 m) range
- True day/night with IR cut filter
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- Wide Dynamic Range (WDR)
- Up-the-coax control (UTC)
- Weatherproof IP67 rated
- Vandal resistant housing IK10 rated
- DC12V or AC24V



CDT2312VIRFW Specifications

Model	Lens (mm)	Resolution
CDT2312VIRFW	2.8 - 12 mm	2 Megapixel

Power		
Source	DC12V or AC24V	
Consumption	850mA @ DC12V IRs On 500mA @ AC24V IRs On	
Sensor and General Information		
Image Sensor	1/2.8" Sony Exmor CMOS	
Scanning Mode	Progressive Scan	
Resolution (H x V)	1920 x 1080	
Len Type	Remote Focus	
Lens Focal Length	2.8 - 12 mm	
Iris Control	DC Auto Iris	
Frame Rate	Up to 30 fps	
IR LEDs	42 LEDs	
IR Range	65 feet (20 m) range	
IR Spectrum	850nm/45° x \sigma5 x 42 IRs	
Minimum Illumination	0 Lux with IRs On	
Shutter Speed	Auto / Manual / Flicker 1/30 ~ 1/30,000	
S/N Ratio	>50 dB	
Video Features		
Video Output	1.0Vp-p, 75Ω Composite 1.0Vp-p, 75Ω TVI	
Camera Functions		
Auto Gain Control	Yes	
Auto White Balance	Yes	
Back Light Compensation	Yes	
Day / Night	Yes; IR cut filter	
Digital Noise Reduction	Yes	
Wide Dynamic Range	Yes	

General Information		
IP Rating	IP67	
IK Rating	IK10	
Humidity	0% ~ 80%	
Temperature	14°F to 122°F (-10°C to 50°C)	
Dimensions (\@ x H)	5.5" x 4.4" x 5.5" (140 x 111 x 140 mm)	
Weight	3.0 lbs. (1400 g)	
Line Drawing		
140mm 77mm 0 360° E 90° 140mm		

