2 Megapixel Outdoor IR TVI Turret **Remote Focus Lens**





Features: Description: The CTT2S12VIFW outdoor turret camera • 2 Megapixel Resolution provides high quality video at 2 megapixel • 1/3" CMOS Image Sensor resolution over existing coaxial cable. The infrared LEDs provide illumination for clear • 15 IR LEDs with an 80 feet (25m) Range image quality at night. The IP66 weatherproof • Back Light Compensation (BLC) rating makes this dome camera suitable for • Digital Noise Reduction (DNR) outdoor applications. Costar's new line of HDTVI • Wide Dynamic Range (WDR) • Up-the-Coax (UTC) cameras are compatible with the ET Series DVRs and StarNET Video Management · Weatherproof IP66 Rated Software. StarNET is the remote access software • 12VDC or 24VAC that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

- 2.8-12mm Remote Focus and Zoom Lens



CTT2S12VIFW Specifications

Model	Lens	Resolution
CTT2S12VIFW	2.8-12mm Motorized Lens	2 Megapixel

Power		
Source	12VDC or 24VAC	
Consumption	4.5 watts (375mA)	
Sensor and General Information		
Image Sensor	1/3" Panasonic CMOS	
Signal System	PAL/NTSC	
Resolution (H x V)	1920x1080	
Lens Focal Length	2.8-12mm Motorized Lens	
Iris Control	Auto Iris	
Frame Rate	PAL:25fps ,NTSC:30fps	
IR LED	15pcs	
IR Wavelength	850nm	
IR Range	80 Feet (25m) Range	
Minimum Illumination	Color:1.0LUX, BW: 0.5 LUX	
	Color:DSS:0.017LUX,	
	BW DSS: 0.0008 LUX	
Shutter Speed	PAL:1/50-1/50000,	
	NTSC:1/60-1/60000	
S/N Ratio	More than 42dB(AGC off)	
Up the Coax	Pelco C, UTC (H)	
Video Features		
Max Distance	985 Feet (300m)	
Video Output	HD-TVI(1080P), HD-AHD(1080P)	
	CVBS(960H)1Vp-p Composite	
	Output(75 Ω /BNC)	
Camera Functions		
Auto Gain Control	0-20 steps	
Brightness	0-20 steps	
Day & Night	Yes, IR Cut Filter	
Defog	Yes	
Motion Detection	Yes	
Digital Noise Reduction	Yes, 3D	
Wide Dynamic Range	120dB (WDR)	

General Information	on	
IP Rating	IP66	
Humidity	85% RH Max	
Temperature	14°F to 131°F	
	(-10°C to 55°C)	
Dimensions	4.72" x 4.15"	
	(120 x 105.5mm)	
Weight	1.543 lbs.	
	(700g)	
Approvals	FCC, CE	
Dimensions		
4.75°		
Accessories		
CDMWMS20	Wall Mount	
CDAJB10	Junction Box	

