## COSTAR VIDEO SYSTEMS

### 1000TVL Analog Bullet Camera



#### Description:

The Costar CBC3112IRv2 has established itself as an outstanding general purpose high resolution camera. With superior image quality, 1000 lines of resolution, and true wide dynamic range, this camera has many years of proven success. The CBC3112IRv2 general purpose 2.8-12mm lens offers the perfect option for wide angle and mid-range viewing solutions. When security performance is critical, depend on the proven quality of Costar bullet cameras.

The CBC3112IRv2 is compatible with Costar Digital Video Recorders (DVRs) that run our free StarNET Video Management Software (VMS). StarNET is the remote access software that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

#### Features:

- 1000 TV Lines of Resolution
- 2.8-12 mm Lens
- DC Auto Iris Lens
- 36 IR LED's
- Day/Night (D/N)
- Wide Dynamic Range (True WDR)
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- Weatherproof IP66 Rated
- 12VDC / 24VAC



# **CBC3112IRv2 Specifications**

Model	Lens	Resolution
CBC3112IRv2	2.8 - 12 mm	1000TVL

Power		
Power Source	DC12V or AC24V	
Power Consumption	1.5 Watts	
Sensor		
Image Sensor	1/3" Sony IMX238 CMOS	
Active Pixels Number	1.3 megapixels	
Scanning Mode	Progressive Scan	
Resolution	1000TVL	
Video Output	1.0 Vp-p75Ω (BNC Output)	
Minimum Illumination	Color: 0.1 Lux	
	B&W: 0.03 Lux at F1.2 IR on 0.0 Lux	
Shutter Speed	1/50 ~ 1/60,000 sec	
S/N Ratio	≥ 55dB	
Camera Functions		
Lens	2.8~12mm ICR Lens	
TV System	NTSC / PAL	
Auto Gain Control	Yes; Auto	
AGC	Auto	
Auto White Balance	Yes	
Sense-up	X2 ~ X64	
Sync. System	Internal	
Gamma Correction	0.45 ~ 0.65	
Digital Noise Reduction	Yes; 3DNR	
Infrared LEDS	Yes, 36 IR LEDs	
Wide Dynamic Range	Yes; Progressive Scan	

General Information	General Information		
<b>-</b> ,	-14°F to +122°F		
Temperature	(-10°C to +50°C)		
Humidity	90% Non Condensing		
Dimensions	11.64" (Ø) x 3.61" (H) 295.7 (Ø) x 91.7 mm (H)		
Weight	2 lbs. ( 950g)		
Dimensions			
102			

