COSTAR VIDEO SYSTEMS







The CDT2S12VIFW outdoor dome camera provides high quality video at 2 megapixel resolution over existing coaxial cable. The infrared LEDs provide illumination for clear image quality at night. The IP66 weatherprorating makes this dome camera suitable for

Description:

infrared LEDs provide illumination for clear image quality at night. The IP66 weatherproof rating makes this dome camera suitable for outdoor applications. Costar's new line of HDTVI cameras are compatible with the ET Series DVRs and StarNET Video Management Software. StarNET is the remote access software that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

Features:

- 2 Megapixel Resolution
- 1/3" CMOS Image Sensor
- 2.8-12mm Remote Focus and Zoom Lens
- 15 IR LEDs with an 65 feet (20m) Range
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- Wide Dynamic Range (WDR)
- Up-the-Coax (UTC)
- · Weatherproof IP66 Rated
- · Impact resistant IK10 Rated
- 12VDC or 24VAC



CDT2S12VIFW Specifications

Model	Lens	Resolution
CDT2S12VIFW	2.8-12mm Motorized Lens	2 Megapixel

Power		
Source	12VDC or 24VAC	
Consumption	4.5 watts (375mA)	
Sensor and General Information		
Image Sensor	1/3" Panasonic CMOS	
Signal System	PAL/NTSC	
Resolution (H x V)	1920x1080	
Lens Focal Length	2.8-12mm Motorized Lens	
Iris Control	Auto Iris	
Frame Rate	PAL:25fps ,NTSC:30fps	
IR LED	15pcs	
IR Wavelength	850nm	
IR Range	65 Feet (20m) Range	
	Color:1.0LUX, BW: 0.5 LUX	
Minimum Illumination	Color:DSS:0.017LUX,	
	BW DSS: 0.0008 LUX	
Shutter Speed	PAL:1/50-1/50000,	
	NTSC:1/60-1/60000	
S/N Ratio	More than 42dB(AGC off)	
Up the Coax	Pelco C, UTC (H)	
Video Features		
Max Distance	985 Feet (300m)	
	HD-TVI(1080P), HD-AHD(1080P)	
Video Output	CVBS(960H)1Vp-p Composite	
1	Output(75 Ω /BNC)	
Camera Functions		
Auto Gain Control	0-20 steps	
Brightness	0-20 steps	
Day & Night	Yes, IR Cut Filter	
Defog	Yes	
Motion Detection	Yes	
Digital Noise Reduction	Yes, 3D	
Wide Dynamic Range	WDR 120dB	

General Information		
Ratings	IP66, IK10	
Humidity	85% RH Max	
Temperature	14°F to 131°F (-10°C to 55°C)	
Dimensions	5.11" x 4.40" (130 x 112mm)	
Weight	1.984 lbs. (900g	
Approvals	FCC, CE	
Dimensions		
5.11"		
Accessories		
CDMWMS10	Wall Mount	
CDMPMS10	Pendant Mount	
CDMCSS10	Recessed Support Plate	
CDJBS10	Junction Box	

