COSTAR VIDEO SYSTEMS

CDT2S12VI

2 Megapixel Outdoor IR TVI Dome





Description:

The CDT2S12VI outdoor dome camera provides high quality video at 2 megapixel resolution over existing coaxial cable. The infrared LEDs provide illumination for clear image quality at night. The IP66 weatherproof rating makes this dome camera suitable for outdoor applications. Costar's new line of HDTVI cameras are compatible with the ET Series DVRs and StarNET Video Management Software. StarNET is the remote access software that allows users to remotely view live and recorded video. StarNET incorporates features such as advanced event notification, map monitoring, system status monitoring and many more.

Features:

- 2 Megapixel Resolution
- 1/3" CMOS Image Sensor
- 2.8-12mm AI Manual Focus Lens
- 12 IR LEDs with an 65 feet (20m) Range
- Back Light Compensation (BLC)
- Digital Noise Reduction (DNR)
- Wide Dynamic Range (WDR)
- Up-the-Coax (UTC)
- Weatherproof IP66 Rated
- 12VDC or 24VAC



101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)


CDT2S12VI Specifications

Model	Lens	Resolution
CDT2S12VI	2.8-12mm	2 Megapixel

Power	
Source	12VDC or 24VAC
Consumption	4.5 watts (375mA)
Sensor and General	
Image Sensor	1/3" Panasonic CMOS
Signal System	PAL/NTSC
Resolution (H x V)	1920x1080
Lens Focal Length	2.8-12mm
Iris Control	Auto Iris
Frame Rate	PAL:25fps ,NTSC:30fps
IR LED	12pcs
IR Wavelength	850nm
IR Range	65 Feet (20m) Range
	Color:1.0LUX, BW: 0.5 LUX
Minimum Illumination	Color:DSS:0.017LUX,
	BW DSS: 0.0008 LUX
Shutter Speed	PAL:1/50-1/50000,
	NTSC:1/60-1/60000
S/N Ratio	More than 42dB(AGC off)
Up the Coax	Pelco C, UTC (H)
Video Features	
Max Distance	985 Feet (300m)
	HD-TVI(1080P), HD-AHD(1080P)
Video Output	CVBS(960H)1Vp-p Composite
	Output(75 Ω /BNC)
Camera Functions	
Auto Gain Control	0-20 steps
Brightness	0-20 steps
Day & Night	Yes, IR Cut Filter
Defog	Yes
Motion Detection	Yes
Digital Noise Reduction	Yes, 3D
Wide Dynamic Range	120dB (WDR)

General Information		
IP Rating	IP66	
Humidity	85% RH Max	
Tamananatura	-10°F to 131°F	
Temperature	(-23°C to 55°C)	
Dimensions	5.11″ x 4.40″	
	(130 x 112mm)	
Weight	1.984 lbs.	
	(900g	
Approvals	FCC, CE	

Dimensions



Accessones	
CDMWMS10	Wall Mount
CDMPMS10	Pendant Mount
CDMCSS10	Recessed Support Plate
CDJBS10	Junction Box



101 Wrangler, Suite 201 • Coppell, Texas 75019 • Phone: 469-635-6800 • Fax: 469-635-6822 • Toll Free: 1-888-694-STAR (7827)

www.costarvideo.com