

## 2 Megapixel Box TVI Camera





Description:	Features:
The CCT2L00 mini box camera provides high	2 Megapixel Resolution
quality video at 2 megapixel resolution over	• 1/2.8" CMOS Image Sensor
existing coaxial cable. Costar's new line of HDTVI	Back Light Compensation (BLC)
cameras are compatible with the ET Series DVRs	Digital Noise Reduction (DNR)
and StarNET Video Management Software.	True Wide Dynamic Range (TWDR)
	Up-the-Coax (UTC)
StarNET is the remote access software that allows	• 12VDC or 24VAC
users to remotely view live and recorded video.	
StarNET incorporates features such as advanced	
event notification, map monitoring, system status	
monitoring and many more.	
	COSTAB

## **CCT2L00 Specifications**

Model	Lens	Resolution
CCT2L00	Not included	2 Megapixel

Power		
	12VDC or 24VAC	
Consumption	2.5 watts (375mA)	
Sensor and General Information		
	1/2.8" Sony CMOS	
Signal System	PAL/NTSC	
Resolution (H x V)	1920x1080	
Lens Focal Length		
Iris Control	DC Auto Iris	
Frame Rate	PAL:25fps ,NTSC:30fps	
IR LED		
IR Wavelength		
IR Range		
	Color DSS: 0.00008 Lux	
Minimum Illumination	BW DSS: 0.00008 Lux	
	BW D22: 0.00008 Eux	
Shutter Speed	Auto/ 1/50 ~ 1/60,000sec	
S/N Ratio	More than 42dB(AGC off)	
	Pelco C, UTC (H)	
Video Features		
Max Distance	UTP:985 FEET (300m)	
	HD-TVI(1080P), HD-AHD(1080P)	
Video Output	CVBS(960H)1Vp-p Composite	
	Output(75 Ω /BNC)	
Camera Functions		
Auto Gain Control	0-20 steps	
Brightness	0-20 steps	
	IR Cut Filter	
	Yes	
Motion Detection	Yes	
Digital Noise Reduction	3D-NR	
Wide Dynamic Range	WDR 120dB	

General Information		
Material	Metal Casing	
Humidity	90% RH Max	
Temperature	-4°F ~ 122°F	
Dimensions WxHxD	2.05" x 2.20" x 3.86"	
Weight	0.48lbs	
Approvals	FCC, CE	
Dimensions		
3.86"		

